

# MAXIMISE YOUR TREATMENT ACCURACY AND SYSTEM PERFORMANCE

with the TherMax blood warmer powered by the PrisMax system

The **TherMax** blood warmer brings an innovative approach to CRRT blood warming, allowing clinicians to set and achieve blood warming targets in a safe and simple manner. The **TherMax** blood warmer is controlled through the intuitive user interface of the **PrisMax** system and delivers effective blood warming for a range of therapies through one device.<sup>1</sup>

- EFFICIENT BLOOD WARMING to maintain patient blood temperature during CRRT therapy
- PRECISE CONTROL of return blood temperature helps to reduce risk of hypothermia
- EASY WARMER MANAGEMENT through the PrisMax system user interface

TherMax Blood Warmer	Fluid Warming
Heats blood directly	Heats fluid, with diminished control of blood temperature
Independent from therapy flow rates	Dependent upon therapy flow rate to achieve target warming levels
Continuous warming	Blood is not warmed during therapy interruptions
Avoids precipitation caused by warming of bicarbonate solutions	Additional risk of precipitating events and de-gassing caused by warming of bicarbonate solutions
Automatically adjusts heating based on estimated return blood temperature to achieve prescribed warming target	Can only set fluid warming temperatures without the ability to monitor or adjust return blood temperature



## **Intelligent Warmer**

The **TherMax** blood warmer uses a bi-directional connection with the **PrisMax** system to meet warming targets. This enables the warmer to continuously respond to changing treatment parameters by automatically adjusting heating to meet the prescribed return blood temperature. Once the prescription is entered, no further management or adjustments are needed.<sup>1</sup>

## **Advanced Safety Features**

The **TherMax** blood warmer includes a number of patient safety features to control temperature, detect leaks, and to ensure the correct setup:<sup>1</sup>

- Automatic adjustment of heating during therapy interruptions to ensure blood is not overheated.
- Reduces risk of thermal haemolysis by limiting the maximum outlet temperature to 42 °C.<sup>2</sup>
- Warmer switches off in case of blood pump stop or communication failure.
- Alarm system integrates with the **PrisMax** system to notify the user if unexpected conditions are encountered such as leakages of the warmer bag or instances in which patient warming cannot be fully delivered due to external factors.



# **New Design**

#### TherMax Device

- Dry heat is delivered by plates
- Controlled via the **PrisMax** system's interface
- Opens for easy cleaning

### TherMax Disposable

- Limited extracorporeal blood volume (27 ml)
- Reduction of clotting by:
  - Patented design of bends and turns
  - Optimised design for inlet and outlet areas

# **Specifications**

nsions
3.3 kg
Approx. 135 mm
Approx. 160 mm
Approx. 350 mm
ity
h all <b>Prismaflex</b> sets excluding HF20
body weight, sleeve warmers are indicated.

Heating Specifications	
Selectable set point temperatures	35 °C to 38 °C (the temperature setting is controlled by the <b>PrisMax</b> system)
Accuracy of temperature (patient return temperature controlled by the <b>PrisMax</b> system)	±0.8 °C at steady state for blood flow rates >150 ml/min ±1.5 °C at steady state for blood flow rates between 50 and 150 ml/min.
Maximum plate temperature	Heater plates are controlled to 45.5 °C
Excessive temperature cut off	Safety cutoff at 46.8 °C
Heating up time (22 °C to 45 °C)	~5 min

For more information, please speak with a Baxter representative.

For safe and proper use of products mentioned herein, please refer to applicable Operators Manual or Instructions for Use

#### References

- 1. Baxter TherMax Operators Manual. AW7006 Rev A 2018;Sep.
- 2. Pouchoulin D. HELIOS/CALIDUS Thermax heating coverage final estimate for initial release. DPN 18.13 Heating coverage from Thermax. Région de Lyon, France: Baxter International Inc.; 2018.